




proposal



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- 2.2>Warning: Working height are not permitted to be less than Min working height.
- 3 Electrical performance
Resistance: 30mOhm Max.
Current rating: 2.0A
- 4 RoHS compliant.

Item	Part name	Qty/Ea'	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.4um plating Ni 1.4um
3	Spring	1	Stainless steel wire	_____
4				
5				

Table 1 Mechanical performance		
Working height	7.10mm	100±20gf <2.1>
Durability	10000cycle	

Top-Link Electronics Ltd.		Type	Unit	Weight		
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Customer drawing	mm		
0.0 = ±0.15		CHK:	Cai wanlu	APVD:	<u>Topo-Link</u> <u>Electronics</u>	
0.00 = ±0.10		REL:			Top-Link Electronics Ltd.	
0.000 = ±0.05						
Angle: ±1°		Name POGO PIN				
SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX. DO NOT SCALE PRINT.						
Scale	Size	DWG No.	Page	Rev.		
1:1	A4	C-101593	1/1	A		