



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 3.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- 3.2>Warning: Working height are not permitted to be less than Min working height.
- 3 Electrical performance
- Resistance: 50mOhm Max.Current rating: 2.0A
- 4 Packaging Spec.Comformance to EIA 481
- 5 RoHS compliant.

Item	Part name	Q'ty/Ea'	Material	Finish
1	HSG	1	High temp.Plastic UL94 V-0 Color Black	_____
2	Body	2	Leaded Brass	Gold plating over Nickel plating
3	Plunger	2	Leaded Brass	Gold plating over Nickel plating
4	Spring	2	Stainless steel wire	_____
5				

Table 1 Mechanical performance		
working height	5.60mm	100gf min<2.1>
Durability	10000cycle	

100352-2  
PART NUMBER

Top-Link Electronics Ltd.	Type	Customer drawing	Unit	mm	Weight
TOLERANCES UNLESS OTHER SPECIFIED	DWN:	Qin Zuozhong	APVD:		
0.0 = ±0.15	CHK:		REL:		
0.00 = ±0.10	Angle: ±1°				
0.000 = ±0.05	SURF. TEXTURE:				
	REMOVE BURRS:				
	BREAK SHARP EDGES				
	RO.05 MAX. DO NOT				
	SCALE PRINT:				
Name	Customer drawing				
Scale	Size	DWG No.			
1:1	A4	C-100352			
Page	1/1	Rev.			
		A			

Top-Link  
Electronics  
Top-Link  
Electronics Ltd.

DIST  
---  
DIST  
---