






THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWG NO. C-100564



Recommended PCB Layout



Notes:
1 Material(材质):
Housing: PA 4,6 (30% Glass Filled)Color Black.
Contact: Brass
Spring: Stainless steel wire

2 Plating:
Body: 0.1um Gold plating over min. 1.4um Nickel plating
(Body 镀 0.1um Min 镍底1.4um Min)
Plunger: 0.4um Gold plating over min. 1.4um Nickel plating
(Plunger 镀 0.4um Min 镍底1.4um Min)

3 Mechanical:
Force: 50gf per pin at 0.8mm stroke
(力: 下压0.8mm的力:110±25gf)
Total stroke(总行程): 1.10mm
Durability(寿命): 10,000 cycle min.

4 Electrical(电性能)
Contact resistance(接触阻抗): 30mOhm Max.
Voltage rating(额定电压): 36V DC Max
Current rating(额定电流): 2.0A

DIMENSIONS IN MM
TOLERANCES UNLESS
OTHER SPECIFIED

0 = ±
0.0 = ±0.15
0.00 = ±0.10
0.000 = ±
ANGLE: ±1°

SURF TEXTURE: 32/

REMOVE BURRS, BREAK
SHARP EDGES R0.05 MAX
DO NOT SCALE PRINT

MATL

HT TR

FIN

DWN
Qin

APVD

REL

NAME

BATTERY POGO CONNECTOR 2 POSITIONS

SCALE

1:1

A4

DWG

NO.

C-100564

SHEET

1 OF 1

REV

1

Top-Link
Electronics Ltd.

100564-2

PART NUMBER

USED ON

-