


proposal



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 3 <2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- 4 <2.2>Warning: Working height are not permitted to be less than Min working height.
- 5 Electrical performance
- 6 Resistance: 30mOhm Max.
- 7 Current rating: 2.0A
- 8 RoHS compliant.

Table 1 Mechanical performance		
Working height	2.90mm	90±30gf <2.1>
Durability	10000cycle	

Item	Part name	Qty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.4um plating Ni 1.4um
3	Spring	1	Stainless steel wire	_____
4				
5				

DIST

A1	Update	2015/12/26
A	NEW	2008/11/11
Rev.	Revision record.	Date.

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight	_____
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Cai wanlu	APVD:	Top-Link Electronics Top-Link Electronics Ltd.		
0.0 = ±0.15 0.00 = ±0.10 0.000 = ±0.05		CHK:		REL:			
Angle: #1: SURF. TEXTURE: REMOVE BURRS BREAK SHARP EDGES R0.05 MAX DO NOT SCALE PRINT.		Name		POGO PIN			
2		Scale	Size	DWG No.		Page	Rev.
		1:1	A4	C-101299		1/1	A1

101299-1
PART NUMBER