



Item	Part name	Qty/Ea	Material	Finish
1	Body	1	Leaded Brass	Gold plating over Nickel plating
2	Plunger	1	Leaded Brass	Gold plating over Nickel plating
3	Spring	1	Stainless steel wire	————
4				
5				

2 Mechanical performance(See the table 1)
 <2>: The force is the average of forces obtained when plunger goes downwards and upwards.

2. **Warning:** Working height are not permitted to be less than min working height.

3 Electrical performance

Resistance: 30mOhm Max.
Current rating: 1.5A

4 RoHS compliant.

DIST --- ---	Rev.	Revision record.	Date.	Top-Link Electronics Ltd TOLERANCES UNLESS OTHER SPECIFIED 0.0 = ± 0.15 0.00 = ± 0.10 0.000 = ± 0.05 Angle: ±1 SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX.DO NOT SCALE PRINT.	Type	Customer drawing	Unit	mm	Weight	_____		
					DIM:	Q in	APVD:	<i>Top-Link Electronics</i> Top-Link Electronics Ltd.				
					CHK:	REL:						
					Name		POGO PIN					
DIST --- ---	Rev.	Revision record.	Date.		Scale	Size	DWG No.	C-101499	Page	1/1	Rev.	1
1:1					A4							