


DIST



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- 3 Electrical performance
Resistance:30mOhm Max.Current rating: 2.0A
- 4 Packaging Spec.Comformance to EIA 481
- 5 RoHS compliant.

Table 1 Mechanical performance

Working height	2.90mm	80±25gf <2.1>
Durability	10000cycle	

Item	Part name	Q'ty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um min over Ni 1.4um min
2	Plunger	1	Leaded Brass	Au 0.1um min over Ni 1.4um min
3	Spring	1	Stainless steel wire	_____
4	CAP	1	High temp,Plastic UL94 V-0 Color Black	_____
5				

Top-Link Electronics Ltd.		Type	Unit	Weight	PART NUMBER	
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Customer drawing	mm	101607-1	
0.0 = ±0.15		CHK:	APVD:		TOP-LINK Electronics	
0.00 = ±0.10		REL:			Top-Link Electronics Ltd.	
0.000 = ±0.005		Name		Customer drawing		
SURF. TEXTURE:		Scale	Size	DWG No.	Page	Rev.
REMOVE SHARP EDGES		1:1	A4	C-101607	1/1	2
BREAK MAX.10 NOT						
SCALE PRINT.						