

|          |          |
|----------|----------|
| DWN No.: | C-101740 |
|----------|----------|

|                                |            |          |
|--------------------------------|------------|----------|
| Table 1 Mechanical performance |            |          |
| Working height                 | 7.00mm     | 80gf min |
| Durability                     | 10000cycle |          |

| Item | Part name | Q'ty/Ea | Material             | Finish                    |
|------|-----------|---------|----------------------|---------------------------|
| 1    | Body      | 1       | Leaded Brass         | Au 0.1um plating Ni 1.4um |
| 2    | Plunger   | 1       | Leaded Brass         | Au 0.4um plating Ni 1.4um |
| 3    | Spring    | 1       | Stainless steel wire | _____                     |
| 4    |           |         |                      |                           |
| 5    |           |         |                      |                           |

Not  
1 Dimensions shall be interpreted per ASME Y14.5M.  
2 Mechanical performance(See the table 1)  
<2.>The force is the average of forces obtained when plunger goes downwards and upwards.  
<2.>Warning: Working height are not permitted to be less than 1.1m working height.  
3 Electrical performance  
Resistance: 30mOhm Max.  
Current rating: 2.0A  
4 RoHS compliant.

|             |
|-------------|
| 101740-1    |
| PART NUMBER |